

What is claimed:

1. A control for controlling a plurality of motors for stopping said motors at a home orientation wherein each of said motors has a first contact, a second contact, and an output shaft, said plurality of motors being configured in a grid having columns and rows with said first contacts of all of said motors in one of said column connected in parallel and said second contacts of all of said motors in one row connected in parallel, wherein one of said plurality of motors in a first column and in a first row is energized by directing electric power across said connector connecting said first connectors of first column and said connector connecting said second connectors of said first row, said controller comprising

a switch on each of said plurality of motors,

said switch having a first contact, a second contact, an open position, and a closed position,

means on said output shaft for actuating said switch when said shaft is at said home orientation,

for each one of said motors, said first contact of said switch connected to said first contact of said motor,

means for detecting a change in electric potential, and

said second contact of said switches of said first row of said plurality of motors connected in parallel and connected to said means for detecting a change in electric potential wherein said means for detecting will detect a change in potential when said shaft of said one of said motors rotates to its said home orientation.

2. The control of claim 1 and further comprising means in series with said switch for preventing a reverse current through said switch.

3. The method of controlling a plurality of motors for stopping said motors at a home orientation wherein each of said motors has a first contact, a second contact, and an output shaft, said plurality of motors being configured in a grid having columns and rows with said first contacts of all of said motors in one of said column connected in parallel and said second contacts of all of said motors in one of said row connected in parallel, wherein one of said plurality of motors in a first column and in a first row is energized by directing electric power across said connector connecting said first connectors of said first column and across said connector connecting said second connectors of said first row, said controller comprising

providing a switch on each of said plurality of motors wherein said switch has a first contact, a second contact, an open position, and a closed position,

providing means on each said output shaft for actuating said switch when said shaft is at said home orientation,

connecting said first contact of said switch to said first contact of said each of said motors,

providing means for detecting a change in electric potential, and

connecting said second contact of said switches of a first row of said plurality of motors in parallel and to said means for detecting a change in electric potential wherein said means for detecting will detect a change in potential when said shaft of said one of said plurality of motors rotates to its said home orientation.

4. The method of claim 3 and comprising the further step of providing means in series with said switch for preventing a reverse current through said switch.

1. In a control for controlling a plurality of motors for stopping said motors at a home orientation wherein each of said motors has a first contact, a second contact, and an output shaft, said plurality of motors being configured in a grid having columns and rows with said first contacts of all of said motors in one of said columns connected in parallel wherein said first contacts of said plurality of motors of a first of said columns are connected through a first switch to a first pole of a source of electric power and said second contacts of all of said motors in a first of said rows are connected through a second switch to a second pole of said source of electric power, wherein one of said plurality of motors in a said first column and in said first row is energized by closing said first and second switches and directing electric power across said first contacts of said first column and said second contacts of said first row, a switch on each of said plurality of motors said switch having a first contact, a second contact, an open condition and a closed condition, and means of said output shaft for actuating said switch when its said shaft is in its said home orientation, the improvement comprising

for each one of said plurality of motors, said first contact of said switch connected to said first contact of said motor,

means for detecting a change in electric potential, and

said second contact of said switches of said first row of said motors connected in parallel to said means for detecting a change in electric potential wherein said means for detecting will detect a change in potential when said first and second switch are

closed and said output shaft of said one of said motors has rotated to its said home orientation.

6. The improvement of claim 5 and further comprising means in series with said switch for preventing a reverse current through said switch.